HARDSCAPE PRODUCTS

www.hardscapeproducts.co.uk
Telephone: 01204 565 500 **Email:** enq@hardscape.co.uk
Hardscape Products Ltd., Eagley House, Deakins Business Park, Egerton, Bolton, Lancashire, BL7 9RP

Natural Stone / Granite / China / Kobra | Grey

Kobra

Grey

Broadly used across the UK for it's consistency and gentle mid-grey hue.

SPECIFICATION	SKU: GRA-CHI-KOB-034	
Material	Granite	
Finish	Bush Hammered, Flamed, Honed, Polished, Sandblasted, Sawn	
Density	-	2770 kg/m³
GWP (total) kgCO2e	ISO 14025 / EN 15804	0.129 per kg
Compressive Strength	BS EN 1926:2006	157 MPa LEV
Compressive Strength (Freeze/Thaw Resistance)	BS EN 1926:2006	171 / 179 MPa Mean
PPV (Before/After)	BS EN 7932:2003	Flamed 71/57, Honed 20/21 PPV
Flexural Freeze/Thaw	BS EN 12371:2010	15.8 / 15.0 MPa Mean
Flexural Strength	BS EN 12372:2006	14.2 MPa LEV
Light Reflectance Value	BS EN 84369:2008	Bush Hammered 23.6 : Flamed 31.1 : Honed 18.8 LRV
Open Porosity	BS EN 1936:2006	0.55%
Slip Resistance	BS EN 13036-4, BS 7976	Bush Hammered 82 (wet), 87 (dry) : Flamed 74 (wet), 80 (dry) SRV/USRV
Water Absorption	BS EN 13755:2008	0.17%
Abrasion Resistance	BS EN 14157:2004	20.8mm



Polished

Sawn

Flamed

CfA ISO 14001 Quality Management UKAS 0120

CfA ISO 9001 Environmental Management UKAS 0120

Ethical Stone Register Declaration Level

Federation Stone Great Britain

NBS Source Manufacturer Partner

Specification & technical data aligns with our most recent testing, but is indicative and should be treated as such. Images are for illustrative purposes only, exact colours may vary.