HARDSCAPE PRODUCTS

www.hardscapeproducts.co.uk
Telephone: 01204 565 500 **Email:** enq@hardscape.co.uk
Hardscape Products Ltd., Eagley House, Deakins Business Park, Egerton, Bolton, Lancashire, BL7 9RP

Portland

Jordans Whitbed

Creamy/white that mellows to grey/white over time, used for external and internal paving, cladding, copings and bespoke carvings, plinths and sculpture work.



SPECIFICATION	SKU: LIM-ENG-POR-008	
Material	Limestone	
Finish	Sawn	
Density	-	2193 kg/m³
GWP (total) kgCO2e	ISO 14025 / EN 15804	0.045 per kg
Compressive Strength	BS EN 1926:2006	37 MPa LEV
Compressive Strength (Freeze/Thaw Resistance)	BS EN 1926:2006	NPD
PPV (Before/After)	BS EN 7932:2003	NPD
Flexural Freeze/Thaw	BS EN 12371:2010	5.25 / 5.15 MPa Mean
Flexural Strength	BS EN 12372:2006	3.6 MPa LEV
Light Reflectance Value	BS EN 84369:2008	Sawn 47.4 : Sawn & 50-Grit 44-59 Range LRV
Open Porosity	BS EN 1936:2006	18.8 %
Slip Resistance	BS EN 13036-4, BS 7976	Sawn (Grit 120) 76 (wet), 87 (dry) SRV/USRV
Water Absorption	BS EN 13755:2008	5.89%
Abrasion Resistance	BS EN 14157:2004	23.4 mm

Sawn

Specification & technical data aligns with our most recent testing, but is indicative and should be treated as such. Images are for illustrative purposes only, exact colours may vary.