Civils & Highways / Active Travel Kerbs / Highway / Highway 180-200

Highway 180-200x250 HD


180-200x250 HD | Return Corner | L-240 | Internal | 135° | Half-Battered | HD

SPECIFICATION

Highway 180-200x250 HD | 180-200x250 HD | Return Corner | L-240 | Internal | 135° | Half-Battered | HD

SKU: ATK-HWC-007-5892

Material	Concrete, Kellen
Finish	Standard, Lavaro, Metallo
Size	180-200(w) x 250(d) x 240(l)
Weight Per Unit	62.51kg
Manufacturing Standard	BS EN 1340:2003
Density	2350 kg/m³
GWP (total) kgCO2e	6.66 kgCO2e/unit
Dutch Ref.	HOEKSTUKKEN-18-20x25xL24-135°-HD-inw
Type	Return Corner Internal
End Style	HD
Profile	180-200x250
Position	-
Face	Half-Battered
Face Angle	81°
Return Angle	135°
Radius	-
Number per 360	-
Slope Angle	-
Slope Gradient	-



Active Travel Kerbs are available in a range of colours, finishes and materials.

Specification & technical data is indicative and subject to change. Images are for illustrative purposes only, details may vary. Some data may vary according to colour / material / finish variation.