Civils & Highways / Active Travel Kerbs / Highway / Highway 180-200

Highway 180-200x250 HD


180-200x250 HD | Transition | to 130-150x250 | L-1000 | Half-Battered | HDHD

SPECIFICATION

Highway 180-200x250 HD | 180-200x250 HD | Transition | to 130-150x250 | L-1000 | Half-Battered | HDHD

SKU: ATK-HWC-007-5978

Material	Concrete, Kellen
Finish	Standard Wet Cast, Lavaro
Size	180-200(w) x 250(d) x 1000(l)
Weight Per Unit	101kg
Manufacturing Standard	BS EN 1340:2003
Density	2350 kg/m³
GWP (total) kgCO2e	10.76 kgCO2e/unit
Dutch Ref.	VERLOOPBANDEN-18-20x25_13-15x25xL100-HD
Type	Transition
End Style	HDHD
Profile	180-200x250
Position	-
Face	Half-Battered
Face Angle	81°
Return Angle	-
Radius	-
Number per 360	-
Slope Angle	-
Slope Gradient	-



Active Travel Kerbs are available in a range of colours, finishes and materials.

Specification & technical data is indicative and subject to change. Images are for illustrative purposes only, details may vary. Some data may vary according to colour / material / finish variation.